

Dosing valves

Series VD type "S" - SMALL

STANDARD

BUROCCO

INDUSTRIAL VALVES srl

BUROCCO INDUSTRIAL VALVES srl VIA NOVEIS, 33 - 13867 PRAY (BI) - ITALY

info@burocco.it - www.burocco.it

Tel.: +39 015 76.72.78 - Fax: +39 015 76.71.36

Technical data

Rating	PN 16
Connections	Female threaded GAS (FF) - ISO 228 Male threaded GAS (FM) - ISO 228 Hose nipple (PG)
Temperature	from +10 to +100 °C

Description

The dosing valves serie VD have been studied and developed to intercept and dose different liquid products (varnishes, solvents, dyes and inks). They can be employed in different fields as textile dyeing and finishing plants, printing, general industrial plants.

Options

⇒ O-ring KALREZ®

Ø Tip	Kvs m ³ /h	Ø Plug	Kvs m ³ /h
0,5 mm	0,003	2,0 mm	0,1
1,6 mm	0,06	7,5 mm	1,5
2,0 mm	0,1	10,0 mm	2,5
4,0 mm	0,3	18,0 mm conical	7



Stroke	
Tip	5,0 mm
Plug	13,0 mm

Dosing valves
Series VD type "S" - SMALL
STANDARD

BUROCCO
INDUSTRIAL VALVES srl

Materials	
Valve body	AISI 316/316L
Tip / plug	AISI 316/316L
Stem	AISI 316/316L
Packing	Standard PTFE ring energized with O-ring FPM
Bushing	PTFE
Body gasket	PTFE
Weight	Kg. 1,2

